

MA-WO55-10NH

4.9-5.875 GHz Omni – Directional Base Station Antenna

MARS 5.8 GHz Base Station Antenna provides a cost effective solution for large scale WLL, WLAN, ISM, MESH Networks and Point-to-Multi Point applications.

UV protected radome suitable for harsh environment installations.

Antenna features stable performance with exceptional 10 dBi of gain.



Specifications

Electrical

Frequency range	4.9-5.875 GHz
GAIN, typ.	10 dBi
VSWR, max.	4.9-5.15 GHz @ 2 : 1 5.15-5.875 GHz @ 1.8 : 1
Polarization	Linear, Vertical
3 dB Beam-Width, H-Plane, typ.	Omni - Directional
3 dB Beam-Width, E-Plane, typ.	10°
Input power, max.	10 Watt
Input Impedance	50 Ohm

Mechanical

Dimensions (HxDia.)	315 x 40 mm (12.4" x 1.6")
Weight	210 gr.
Connector	N-Type, Female / N-Type, Male (optional)
Radome	UV Protected Polycarbonate
Mount	2" PM (End) Attachment

Environmental

Operating Temperature Range	-40°C to +65°C
Vibration	According to IEC 60721-3-4
Wind Load	200 km/h (survival)
Flammability	UL94
Water Proofing	IP-67
Humidity	ETS 300 019-1-4, EN 302 085 (annex A.1.1)
Salt Fog	According to IEC 68-2-11
Ice and Snow	25mm radial (survival)

Ordering Options

MA-WO55-10NH	Antenna with N-Type, Female Connector
MA-WO55-10NHM	Antenna with N-Type, Male Connector

Patterns are available on our website

MARS Antennas & RF Systems proprietary information

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product, available on MARS website.

3 Hamanor st. Holon 5886103, P.O.Box 1852 Holon 5811801, Israel

Tel: +972-3-5599661 • Fax: +972-3-5599677 • e-mail: mars@marsant.co.il • web: www.mars-antennas.com